

# TRUCK&BUS TIRES

2020

 **CONSTANCY**  
NEW ROADS AHEAD **Tire**



## LONG HAUL



## REGIONAL



## ON & OFF



## MINING



## LONG HAUL

### ECOSMART12

#### POSITION



- Possess excellent high-speed driving performance.
- Reduce uneven wear.
- Effectively reduce rolling resistance, and improve tire's drainage and stability performance.
- Low noise and high wear resistance.



Size	PR	LI	SS	Standard Rim	OTD (mm)
11R22.5	14	144/142	M	8.25	14.0
11R22.5	16	146/143	M	8.25	14.0
11R24.5	14	146/143	M	8.25	14.0
11R24.5	16	148/146	M	8.25	14.0
215/75R17.5	18	135/133	J	6.00	12.5
235/75R17.5	18	143/141	J	6.75	12.5
225/70R19.5	14	128/126	M	6.75	12.5
245/70R19.5	16	136/134	M	7.50	12.5
265/70R19.5	16	140/138	M	7.50	12.5
265/70R19.5	18	143/141	J	7.50	12.5
285/70R19.5	16	148/145	M	8.25	13.0
285/70R19.5	18	150/148	J	8.25	13.0
265/70R22.5	16	140/137	M	7.50	14.0
275/70R22.5	16	144/141	M	8.25	14.0
275/70R22.5	18	148/145	M	8.25	14.0
295/75R22.5	14	144/141	M	9.00	14.0
295/75R22.5	16	146/143	M	9.00	14.0
285/75R24.5	14	144/141	M	8.25	14.0
285/75R24.5	16	146/143	M	8.25	14.0



### ECOSMART72

#### POSITION



- Fuel efficient tire with lower rolling resistance characteristics.
- Excellent traction and wet weather handling.
- Optimised tread design and tread depth for long-life properties.



Size	PR	LI	SS	Standard Rim	OTD (mm)
315/80R22.5	20	156/150	M	9.00	15.0



### ECOSMART22

#### POSITION



- Provide a longer mileage.
- Provide excellent driving and grips performance.
- Enhance the grips performance on wet roads.
- Reduce tread heat generation, and deliver excellent durability.



Size	PR	LI	SS	Standard Rim	OTD (mm)
11R22.5	14	144/142	M	8.25	21.0
11R22.5	16	146/143	M	8.25	21.0
11R24.5	14	146/143	M	8.25	21.0
11R24.5	16	149/146	M	8.25	21.0
295/75R22.5	14	144/141	M	9.00	21.0
295/75R22.5	16	148/143	M	9.00	21.0
285/75R24.5	14	144/141	M	8.25	21.0
285/75R24.5	16	146/143	M	8.25	21.0



### ECOSMART36

#### POSITION



- Possess excellent high-speed driving performance.
- Reduce uneven wear.
- Effectively reduce rolling resistance, and improve tire's drainage and stability performance.
- Suitable for long distance ride.



Size	PR	LI	SS	Standard Rim	OTD (mm)
11R22.5	14	144/142	M	8.25	11.0
11R22.5	16	146/143	M	8.25	11.0
295/75R22.5	14	144/141	M	9.00	11.0
295/75R22.5	16	146/143	M	9.00	11.0



### ECO96

#### POSITION



- Better handling and driving stability at high speed driving.
- Four straight grooves design provides excellent wet resistance.
- Excellent heat dissipation, low noise.



Size	PR	LI	SS	Standard Rim	OTD (mm)
11.00R20	18	152/149	L	8.0	15.0

## GRD-1313

### POSITION



- The design in the middle of the tread provides good steering and anti-sideslip performance.
- The wider tread design and high wear resistance formula ensures excellent wear resistance.
- Optimized contour design ensures uniform force on each block of tread and prevents irregular wear.
- The use of highly strengthened tire carcass and steel belt greatly improves the service life of tires.



Size	PR	LI	SS	Standard Rim	OTD (mm)
11R22.5	16	146/143	L	8.25	21.5

## REGIONAL

## ECOSMART62

### POSITION



- Ensure excellent wear resistance performance.
- Effectively prevent the sideslip and provide good handling performance.
- Good heat dissipation and stone anti-pinch performance.
- Reduce tread heat generation, and deliver excellent durability.
- Provide excellent wear resistance performance.



Size	PR	LI	SS	Standard Rim	OTD (mm)
11R22.5	16	146/143	M	8.25	15.0
• 12R22.5	18	152/149	M	9.00	16.0
315/80R22.5	20	156/150	M	9.00	16.0
295/80R22.5	18	152/149	M	9.00	15.0
295/80R22.5	18	152/149	M	9.00	15.0
275/80R22.5	16	149/146	M	8.25	14.0
315/70R22.5	18	152/148	M	9.00	15.0

• With special pattern number ECOSMART62+



## ECOSMART66

### POSITION



- Provide excellent anti-skid and handling performance.
- Effectively increase tire's driving performance, reduce heat generation and improve durability.
- Reduce tread heat generation, and deliver excellent durability.
- Provide excellent wear resistance performance.



Size	PR	LI	SS	Standard Rim	OTD (mm)
385/65R22.5	20	160	K	11.75	15.0
385/55R22.5	20	160	K	12.25	15.0
425/65R22.5	20	165	K	12.25	15.0
445/65R22.5	20	169	K	13.00	15.0



## ECOSMART78

### POSITION



- Provide powerful driving and drainage performance.
- Improve the rigidity of tire's shoulder and prevent chipping.
- Greatly prolong tire's life.
- Add wear volume and improve wear resistance.



Size	PR	LI	SS	Standard Rim	OTD (mm)
11R22.5	16	146/143	M	8.5	20.0
12R22.5	18	152/149	M	9.00	20.0
215/75R17.5	16	126/124	M	6.00	15.0
215/75R17.5	18	135/133	J	6.00	15.0
235/75R17.5	16	132/130	M	6.75	15.0
235/75R17.5	18	143/141	J	6.75	15.0
225/70R19.5	14	128/126	M	6.75	15.0
245/70R19.5	16	136/134	M	7.50	15.0
265/70R19.5	16	140/138	M	7.50	15.0
265/70R19.5	18	143/141	J	7.50	15.0
285/70R19.5	16	148/145	M	8.25	16.0
285/70R19.5	18	150/148	J	8.25	16.0
275/80R22.5	16	149/146	M	8.25	19.0
295/80R22.5	18	152/149	M	9.00	20.0
315/70R22.5	18	152/148	M	9.00	20.0
315/80R22.5	18	154/151	M	9.00	20.0
315/80R22.5	20	156/150	M	9.00	20.0



## ECO65

### POSITION



- Optimized profile avoids the uneven wear efficiently.
- Special groove design enhances the gripping power on wet ground.
- Deepened semi-open shoulder design improves the driving performance.



Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	M	9.00	22.0

## ECOSMART79

### POSITION



- Grooves geometry optimised to ease self-cleaning, thus ensuring better traction and even wear.
- Added protection at the bottom of grooves to avoid stone trapping and give better resistance.
- Aggressive directional tread with robust tread blocks providing extra traction for various road condition.



Size	PR	LI	SS	Standard Rim	OTD (mm)
13R22.5	18	156/150	L	9.75	17.5
315/80R22.5	20	156/150	M	9.00	20.0



## ECOSMART88

### POSITION



- 10% Bigger tread width enlarges the footprint and improves the mileage.
- Wider tread design improves comfort and avoids the irregular wear efficiently.



Size	PR	LI	SS	Standard Rim	OTD (mm)
315/80R22.5	18	154/151	M	9.00	21.0
315/80R22.5	20	156/150	M	9.00	21.0





## ECOSMART92

### POSITION



- Grooves geometry optimised to ease self-cleaning, thus ensuring better traction and even wear.
- Added protection at the bottom of grooves to avoid stone trapping and give better resistance.
- Aggressive directional tread for wet road tread blocks providing extra traction for various road condition.

Size	PR	LI	SS	Standard Rim	OTD (mm)
12.00R24	20	160/157	K	8.5	14.5



## ECOSMART97

### POSITION



- Three vertical grooves in winding provide good driving performance, suitable for middle and long distance, steer or trailer wheel recommended.
- Narrow grooves reinforce the drainage of water and prevent sideslip.
- Closed tire shoulder reduces economic wear and enhances driving handling.
- Unique design for the carcass ply and tread belt improves the performance for overload and safety.

Size	PR	LI	SS	Standard Rim	OTD (mm)
12.00R24	20	160/157	K	8.5	14.5



## ECOSMART98

### POSITION



- Block pattern design provides strong traction and excellent wear resistance.
- Half-open shoulder and wide transverse groove provides strong driving force, excellent gripping ability in dry and wet road condition.
- Unique tread compound design provides excellent mileage.

Size	PR	LI	SS	Standard Rim	OTD (mm)
12.00R24	20	160/157	K	8.5	15.5



## ECOSMART77

### POSITION



- Deliver high efficiency and environment protection.
- Constant grips and handling performance on wet roads.
- Provide a comfortable, safe and fuel saving ride.
- Provide better driving and wear resistance performance.

Size	PR	LI	SS	Standard Rim	OTD (mm)
425/65R22.5	20	165	J	12.25	17.5
445/65R22.5	20	169	K	13.00	18.0



## ON & OFF



## M3

### POSITION



- Excellent pattern design combines with excellent traction and braking performance.
- Tire tread grooves have heat dissipation efficiency and excellent drainage performance.
- Special formula of structure lowers rolling resistance, good wear resistance and reduces oil consumption.

Size	PR	LI	SS	Standard Rim	OTD (mm)
11.00R20	18	152/149	K	8.00	16.0
12.00R20	20	156/153	K	8.50	16.0



## GR775

### POSITION



- It is suitable for short or medium distance on different road conditions.
- Special pattern design provides good traction, transmission performance and excellent wear resistance.
- Reinforced carcass ensures longer mileage.

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	K	9.00	16.5



## ECO61

### POSITION



- Provide a longer mileage.
- Provide excellent steering and anti-skid performance.
- Ensure good stone removing performance and prevent tread groove cracking.
- Reduce tread heat generation, and deliver excellent durability.
- Provide excellent wear resistance performance.

Size	PR	LI	SS	Standard Rim	OTD (mm)
11R22.5	16	146/143	M	8.25	17.5
12R22.5	18	152/149	M	9.00	18.0
13R22.5	18	154/151	M	9.75	20.0
315/80R22.5	20	156/150	M	9.00	18.0



## ECO63

### POSITION



- Strong construction improves both high speed and heavy load performance.
- Deepened tread design assures the longer life.
- Lateral grooves provide strong driving power.

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	M	9.00	19.0



## ECOSMART82

### POSITION



- Mixed deepen block tread and widen tread cap enhance tyre's grip performance.
- Design for anti-stone in bottom of tread prevent cutting for inner groove on bad road condition.
- Optimized and reinforced tire bead strengthen overloading ability.

Size	PR	LI	SS	Standard Rim	OTD (mm)
12.00R24	20	160/157	K	8.5	20.0
325/95R24	22	162/160	K	9.0	20.0



# MINING

## ECOSMART81

### POSITION



- The large and deep grooves on the shoulder is designed to increase the driving performance.
- Three main longitudinal grooves provide good directional stability and reduce irregular wear and are adapted to various road.
- Widened running surface and the puncture resistance formula are characterized by excellent resistance to puncture and to abrasion.

Size	PR	LI	SS	Standard Rim	OTD (mm)
6.50R16LT	12	110/105	M	5.50F	9.0
7.00R16LT	14	118/114	M	5.50F	10.5
7.50R16LT	14	122/118	L	6.00G	13.0
8.25R16LT	16	128/124	L	6.50H	13.0
9.00R20	16	144/142	L	7.00	15.5
10.00R20	18	149/146	L	7.50	16.5
11.00R20	18	152/149	L	8.00	17.0
12.00R20	20	156/153	L	8.50	16.5
11R22.5	18	148/145	M	8.25	15.0
12R22.5	18	152/149	M	9.00	16.0
13R22.5	18	156/150	L	9.75	17.0
285/70R19.5	18	143/141	M	7.50	15.0
315/80R22.5	20	156/150	M	9.00	16.0
11R24.5	16	149/146	M	8.25	15.0
12R24.5	18	154/151	K	9.00	16.0
12.00R24	20	160/157	K	8.50	17.5
* 12.00R24-1N	20	160/157	K	8.50	17.5

\* 1N Adding one layer of nylon wrapper can effectively enhance the strength of the bead and improve the anti-load performance.



## ECOSMART81

### POSITION



- Deepened tread design assures the extra-long driving mileage.
- High resistance to cutting and abrasion.
- V groove design to protect groove bottom effectively.

Size	PR	LI	SS	Standard Rim	OTD (mm)
11.00R20	18	152/149	L	8.00	16.5
12.00R20	20	156/153	L	8.50	18.0



## ECO85

### POSITION



- Big block with strong body provides excellent cut resistance performance.
- Strong construction improves load performance.
- Deepened grooves assure the long life.
- Big open shoulder provides good self-cleaning ability.

Size	PR	LI	SS	Standard Rim	OTD (mm)
11.00R20	18	152/149	E	8.00	23.0
12.00R20	20	156/153	E	8.50	24.0



## ECO86

### POSITION



- Deliver excellent wear, cut and tear resistance performance.
- Prolong tire's life.
- Ensure good stone removing performance and prevent tread groove cracking.
- Possess cut resistance, no-chunking and no chipping effects.

Size	PR	LI	SS	Standard Rim	OTD (mm)
11.00R20	18	152/149	E	8.00	24.5
12.00R20	20	156/153	E	8.50	25.5



## GR869

### POSITION



- Unique block design combines with good driving performance and braking performance.
- High wear resistance formula delivers tear resistance, wear resistance and high mileage.
- Strengthened tire carcass and belt provide good load resistance.

Size	PR	LI	SS	Standard Rim	OTD (mm)
12.00R20	20	156/153	K	8.50	19.0



## M5

### POSITION



- Excellent pattern design delivers better driving force and road holding.
- Optimized and strengthened bead design combines with excellent load capacity.
- High wear resistance, low heat generation and deeper groove pattern improve the service life of tires.

Size	PR	LI	SS	Standard Rim	OTD (mm)
11.00R20	18	152/149	K	8.00	18.5
12.00R20	20	156/153	K	8.50	18.0



## MD888

### POSITION



- Large block pattern combines with excellent anti-cutting performance.
- The reinforced carcass structure has excellent load performance.
- Typical transverse pattern groove has excellent climbing and passing performance.

Size	PR	LI	SS	Standard Rim	OTD (mm)
12.00R20	20	156/153	E	8.50	25.5

International



Europe



E MARK CERTIFICATION

USA



DEPARTMENT OF TRANSPORT

China



CERTIFICATE OF COMPULSORY PRODUCT



**YUELONG  
RUBBER**

---

**YUELONG TIRE GROUP**

Web: [www.yuelonggroup.net](http://www.yuelonggroup.net)

Email: [info@yuelonggroup.net](mailto:info@yuelonggroup.net)

---

**DISTRIBUTED BY**