

TYRE CATALOGUE

ALL STEEL TRUCK & BUS RADIAL TYRE





TH051

POSITION



- The brand new profile design adapts to the lightweight requests of market with standard load and improves the cost-effectiveness of tires.
- The use of new Bekaert UT steel wire ensures the strength of the tire while reducing the weight and improves the durability of the carcass.
- The design of three zigzag grooves increases the saturation of pattern and improves the wear resistance of the tire.

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	L	9.00	15.0

FH052

POSITION



- The brand new profile design adapts to the lightweight requests of market with standard load and improves the cost-effectiveness of tires.
- The use of new Bekaert UT steel wire ensures the strength of the tire while reducing the weight and improves the durability of the carcass.
- The design of linear pattern improves drainage and handling performance.

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	L	9.00	15.0

DM357

POSITION



- The design of connecting ribs between the blocks and the strengthening structure on the shoulder provides strong driving and braking performance.
- Deep pattern and narrow tread make the tire more fuel-efficient.
- The unique design of tread compound makes the tire have excellent wear-resisting performance.

Size	PR	LI	SS	Standard Rim	OTD (mm)
11R22.5	16	146/143	L	8.25	21.5

DM59

POSITION



- 27.5mm wider tread cap and 24.5mm deeper grooves improve wear resistance and service life.
- Scientific tread compound reduces abrasion rate. Low rolling resistance is fuel-saving.
- Long hexagonal pattern blocks and strong bead wires deliver longer service life and reduce damages.
- High bridges of shoulder ribs prevent scrubbing. Pattern blocks with double wavy sipes deliver extra traction.

Size	PR	LI	SS	Standard Rim	OTD (mm)
11R22.5	16	146/143	L	8.25	21.5
315/80R22.5	20	156/150	L	9.00	24.5

SH57

POSITION



- 26.5mm wider tread cap leads to excellent wear resistance and long mileage.
- Innovative 3D pattern with variable angle expels stones and avoids groove cracking.
- Four longitudinal grooves provide low rolling resistance and excellent steering performance.
- Advanced cut-resistant tread compound provides outstanding wear resistance.

Size	PR	LI	SS	Standard Rim	OTD (mm)
315/80R22.5	20	156/150	L	9.00	16.5

SH55

POSITION



- Excellent anti-sideslip performance, low rolling resistance and noise.
- Enclosed shoulders prevent the tyres from eccentric wear.
- Four longitudinal grooves and smooth shoulders deliver outstanding high-speed performance.

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	M	9.00	17.0
315/80R22.5	20	156/150	M	9.00	15.0

896

POSITION



- The large and deep grooves on the shoulders aim to increase the driving performance.
- Three main longitudinal grooves provide good directional stability and reduce irregular wear and are adapted to various conditions.
- Wider running surface and the puncture resistance formula reduce abrasion.

Size	PR	LI	SS	Standard Rim	OTD (mm)
6.50R16LT	14	110/105	M	5.50F	12.5
7.00R16LT	14	114/118	L	5.50F	12.5
7.50R16LT	14	122/118	L	6.00G	13.5
8.25R16LT	16	128/124	L	6.50H	13.5
8.25R20LT	16	139/137	K	6.50	13.0
9.00R20	16	144/142	K	7.0	15.5
10.00R20	18	149/146	K	7.5	16.5
11.00R20	18	152/149	K	8.0	17.0
12.00R20	20	156/153	K	8.5	17.5
12.00R24	20	160/157	K	8.5	15.0
▲ 11R22.5	18	146/143	M	8.25	15.0
12R22.5	18	152/149	M	9.00	17.0
13R22.5	18	154/151	L	9.75	17.5
315/80R22.5	20	156/150	M	9.00	16.0
▲ 325/95R24	22	162/160	K	9.00	17.5

▲ With special pattern name AH96

ECOSMART81

POSITION



- The large and deep grooves on the shoulders aim to increase the driving performance.
- Three main longitudinal grooves provide good directional stability and reduce irregular wear and are adapted to various conditions.
- Wider running surface and the puncture resistance formula reduce abrasion.

Size	PR	LI	SS	Standard Rim	OTD (mm)
11R24.5	16	149/146	M	8.25	15.5
12R24.5	18	154/151	K	9.00	16.5

698

POSITION



- Four zigzag grooves and robust longitudinal ribs are designed to reduce braking distance and to enhance driving safety.
- Ejectors at the bottom of grooves prevent stones trapping.
- Innovative compound of shoulders reduce pattern contact pressure and irregular wear to increase mileage.



Size	PR	LI	SS	Standard Rim	OTD (mm)
11R22.5	16	146/143	M	8.25	15.0
12R22.5	18	152/149	M	9.00	15.0
295/80R22.5	18	152/149	M	9.00	15.0
315/80R22.5	20	156/150	M	9.00	15.0

903

POSITION



- The three middle grooves provide good guiding and drainage properties, which are suitable for guiding and drag wheel position.
- Using the low heat rubber in the tyre tread base ensures excellent durability and wear & cut resistance.
- The upper tread rubber formula ensures the excellent cut, tear and abrasion resistance.



Size	PR	LI	SS	Standard Rim	OTD (mm)
11R22.5	16	146/143	L	8.25	18.0
12R22.5	18	152/149	L	9.00	18.5
13R22.5	18	154/151	L	9.75	20.5

982

POSITION



- Big angle of the grooves avoid transformation and cracking.
- Variable angle of groove bottom will effectively prevent stone retention and improve service life.
- Arc shape of the grooves makes the pattern look better and keep rigidity.
- The middle sipes aims to balance load and wear and to avoid groove bottom cracking.



Size	PR	LI	SS	Standard Rim	OTD (mm)
12.00R24	20	160/157	K	8.5	14.5

667

POSITION



- Four longitudinal grooves with zigzag sipes deliver outstanding operation and traction.
- Outer profile design helps to minimize irregular wear.
- Reinforced bead allows better resistance to impacts and load.
- Wider running surface with special compound leads to anti-puncture and anti-abrasion.



Size	PR	LI	SS	Standard Rim	OTD (mm)
315/80R22.5	20	156/150	M	9.00	18.0

668

POSITION



- Wider and horizontal grooves greatly improve self-cleaning ability and driving performance.
- The interconnecting ribs between pattern blocks reduce the movement and decrease partial wear.
- High wear resistance and low heat generation of the tread rubber ensure long service life.



Size	PR	LI	SS	Standard Rim	OTD (mm)
11R22.5	16	146/143	L	8.25	20.0
12R22.5	18	152/149	L	9.00	20.0
295/80R22.5	18	152/149	L	9.00	20.0
315/80R22.5	20	156/150	L	9.00	20.0

866

POSITION



- Optimized pattern reduces noise generation, tread block movement and fuel consumption.
- The geometric design of grooves and siping promote steering precision and excellent dry and wet handling.
- Reinforced bead allows better resistance to impacts and load.



Size	PR	LI	SS	Standard Rim	OTD (mm)
315/80R22.5	20	156/150	M	9.00	15.0

828

POSITION



- Three vertical grooves in winding provide good driving performance, which are suitable for middle and long distance. Steer or trailer wheel is recommended.
- Narrow grooves reinforce the drainage and prevent sideslip.
- Closed shoulders reduce eccentric wear and enhance driving handling.
- Unique design of the carcass ply and tread belt improves safety and the performance of overload.



Size	PR	LI	SS	Standard Rim	OTD (mm)
315/80R22.5	20	156/150	M	9.00	15.0
12.00R24	20	160/157	K	8.5	14.5

886

POSITION



- The geometric design of grooves ensures easy self-cleaning, better traction and even wear.
- Added protection at the bottom of grooves effectively avoids stone trapping and gives better resistance.
- Aggressive directional tread with robust blocks provides extra traction for various road conditions.



Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	L	9.00	18.0
13R22.5	18	156/150	L	9.75	18.0
315/80R22.5	20	156/150	L	9.00	20.0

688

POSITION



- The structure of 5 zigzag grooves provides excellent traction and directional driving performance, as well as cornering stability.
- Specialized tread formula and optimized design provide the tyres with excellent mileage and balancing.
- Ladder-like shoulders effectively reduce heat and prevent uneven wear.



Size	PR	LI	SS	Standard Rim	OTD (mm)
385/65R22.5	20	160	K	11.75	14.5



DM55

POSITION



- Transverse and wide grooves provide outstanding traction performance.
- Longitudinal grooves improve the performance of drainage and heat dissipation.
- Cutting resistance compound is suitable for various road conditions.
- Wider tread cap and deeper grooves provide excellent wear resistance.

Size	PR	LI	SS	Standard Rim	OTD (mm)
9.5R17.5	18	143/141	L	6.75	15.0
11R22.5	16	146/143	K	8.25	21.5
12R22.5	18	152/149	L	9.00	22.5



DM58

POSITION



- Big block pattern protects the tyres against wear, cut and tear.
- Wider tread cap effectively increase mileage.
- Anti-clamping stone design prevents from groove cracking.
- Special mining compound protects against puncture, chunking and chipping.

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	J	9.00	22.5



TH58

POSITION



- Excellent anti-sideslip performance, low rolling resistance and noise.
- Enclosed shoulders prevent the tyres from eccentric wear.
- Four zigzag longitudinal grooves provide excellent directional driving performance and avoid groove cracking.

Size	PR	LI	SS	Standard Rim	OTD (mm)
11R22.5	16	146/143	M	8.25	14.5



YL661

POSITION



- Three zigzag longitudinal grooves enhance handling stability.
- Special compound and optimized pattern provide excellent wear resistance.
- Stone ejection design of the grooves delivers outstanding puncture resistance and reduces crack.

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	M	9.00	15.0



YL662

POSITION



- Wider and deeper pattern and optimized cap profile provide long service life and make it more cost-effective.
- Four zigzag grooves, solid longitudinal ribs and special sipes make it safe, comfortable, ski-proof and fuel-efficient.
- High-tensile casing steel cord delivers durability and retard ability.

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	M	9.00	15.0



YL608

POSITION



- Wider running surface with special compound ensures anti-puncture and anti-abrasion.
- Optimized width of groove shape and ribs minimizes strain at groove bottom.
- Minimal variation of pattern shape reduces irregular wear and increase load resistance.
- Four longitudinal grooves with wavy sipes improve handling and traction.

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	L	9.00	21.0



699

POSITION



- Four longitudinal grooves are adopted for excellent handling stability and ride comfort at high speed.
- Horizontal grooves and special tiny sipes on the tread improve drainage performance and skid resistance.
- New tread formula is created for outstanding abrasion resistance.

Size	PR	LI	SS	Standard Rim	OTD (mm)
11R22.5	16	146/143	M	8.25	16.0
12R22.5	18	152/149	M	9.00	16.5



ECOSMART62

POSITION



- Four longitudinal grooves are adopted for excellent handling stability and ride comfort at high speed.
- Horizontal grooves and special tiny sipes on the tread improve drainage performance and skid resistance.
- New tread formula is created for outstanding abrasion resistance.

Size	PR	LI	SS	Standard Rim	OTD (mm)
275/80R22.5	16	149/146	M	8.25	14.0
295/80R22.5	18	152/149	M	9.00	15.0
315/70R22.5	18	152/148	M	9.00	15.0
315/80R22.5	20	156/150	M	9.00	16.0



FC33

POSITION




- Increased sidewall duration and low rolling resistance.
- Extreme ease in measuring sidewall wear.
- Improved grip on wet and slippery surfaces.

Size	PR	LI	SS	Standard Rim	OTD (mm)
9.5R17.5	18	143/141	L	6.75	13.5
215/75R17.5	18	135/133	L	6.00	12.0
235/75R17.5	18	143/141	L	6.75	13.0
295/80R22.5	18	152/149	M	9.00	16.0
11R22.5	18	148/145	M	8.25	13.5
11R24.5	18	149/146	M	8.25	13.5



DH39

POSITION



- Lower operating temperatures benefit tyre integrity and retreadability.
- Increased resistance to tears and lacerations.
- Less possibility of accidental casing damage.

Size	PR	LI	SS	Standard Rim	OTD (mm)
215/75R17.5	18	135/133	L	6.00	15.5
235/75R17.5	18	143/141	L	6.75	16.0



DM36

POSITION



- Optimized tread block pitch sequence offers better traction and acoustic comfort.
- Optimized design to reduce noise generation.
- Optimum grip on various road conditions.

Size	PR	LI	SS	Standard Rim	OTD (mm)
295/80R22.5	18	152/149	L	9.00	20.0



DM051

POSITION



- The geometric design of grooves ensures easy self-cleaning, better traction and even wear.
- Added protection at the bottom of grooves effectively avoids stone trapping and gives better resistance.
- Aggressive directional tread with robust blocks provides extra traction for various road conditions.

Size	PR	LI	SS	Standard Rim	OTD (mm)
13R22.5	18	154/151	K	9.00	20.5



FH091

POSITION



- The novel medium blocks design with small circumferential grooves in the middle increase the integrity of the pattern.
- Drop-shaped grooves on the shoulder reduce the risk of uneven wear and heat generation.
- Stepped grooves have excellent stone ejection performance.

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	L	9.00	17.0



TH082

POSITION



- Excellent anti-sideslip performance, low rolling resistance and noise.
- Enclosed shoulders prevent the tyres from eccentric wear.
- Four longitudinal grooves and smooth shoulders deliver outstanding high-speed performance.

Size	PR	LI	SS	Standard Rim	OTD (mm)
295/60R22.5	18	150/147	L	9.00	15.5



ZY81

POSITION



- The VAI wear indicator system helps drivers evaluate tire wear and identify early irregular wear problems. The crown is designed with a spring sleeve to ensure a good appearance.
- The proportion of grooves and blocks was readjusted to reduce crown deformation after inflation.
- The increased lines on the pattern grooves effectively prevent stone retention.

Size	PR	LI	SS	Standard Rim	OTD (mm)
12.00R20	20	156/153	J	8.5	17.0



TM061

POSITION



- The novel three-line pattern has excellent driving performance.
- Reinforced materials of carcass improve load capacity.

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	L	9.00	17.0



TH092

POSITION



- It has excellent anti-slip performance and low rolling resistance.
- Closed shoulder design is of low noise and reduce tire wear.
- The crown is designed with a spring sleeve to make the tire look more beautiful.

Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	L	9.00	17.0



AH398

POSITION



- Provide excellent anti-skid and handling performance.
- Effectively increase tire's driving performance, reduce heat generation and improve durability.
- Reduce tread heat generation, and deliver excellent durability.
- Provide excellent wear resistance performance.



Size	PR	LI	SS	Standard Rim	OTD (mm)
385/65R22.5	24	160	K	11.75	14.5

669

POSITION



- Horizontal block pattern provide excellent traction and braking ability.
- Opened shoulders with good self-cleaning ability reduce heat generation.
- Unique compound enhances tyres' speed performance and driving distance.



Size	PR	LI	SS	Standard Rim	OTD (mm)
12R22.5	18	152/149	L	9.00	19.0

YL918

POSITION



- Solid block pattern on the shoulders and optimized longitudinal and lateral grooves provide superior grip performance, which are safe, durable and powerful.
- Low heat generation of tread compound and opened shoulders avoid shoulder separation.
- Reinforced bead and strong casing ensure high quality and performance under heavy load conditions.



Size	PR	LI	SS	Standard Rim	OTD (mm)
12.00R20	20	156/153	K	8.25	18.0

D7

POSITION



- Large lateral tread provides strong traction and prominent performance for the off-road.
- Reinforced tire bead and special designed mining pattern are suitable for bad road conditions and overloading.
- Good property of self-cleaning and high gripping performance suits for muddy road.



Size	PR	LI	SS	Standard Rim	OTD (mm)
11R22.5	16	146/143	E	8.25	19.5

AH23

POSITION



- Bionic pattern provides excellent driving and braking performance.
- Four advanced longitudinal grooves and pressure control technology ensure comfortable driving experience.
- Abrasion-resistant compound provides long mileage and prevents from eccentric wear.



Size	PR	LI	SS	Standard Rim	OTD (mm)
7.50R16	14	122/118	L	6.00G	13.5

YL919

POSITION



- Reinforced carcass, bead and 0 angle structure on the shoulders provide high quality and good performance under heavy load conditions.
- Lateral grooves with wide angles increase driving power and self-cleaning ability.
- Thickened sidewall enhances cut and impact resistance. Strengthened groove bottom enhances puncture resistance on unpaved road.



Size	PR	LI	SS	Standard Rim	OTD (mm)
10.00R20	18	149/146	E	7.50	21.5
11.00R20	18	152/149	E	8.00	21.5
12.00R20	20	156/153	E	8.50	21.5

TK032

POSITION



- Reinforced structural design greatly improves the safety performance of tires.
- Unique pattern on the crown delivers good appearance.
- Stepped grooves on the tread deliver good anti-puncture performance and stone-ejection.



Size	PR	LI	SS	Standard Rim	OTD (mm)
12.00R20	20	152/149	E	8.5	26.0

868

POSITION



- Unique block pattern provides excellent traction and braking performance.
- Cut resistant and low heating-up formula deliver outstanding mileage.
- Robust carcass provides maximum load-bearing capacity.
- Optimized tread effectively improves its self-cleaning ability.



Size	PR	LI	SS	Standard Rim	OTD (mm)
10.00R20	18	149/146	K	7.50	20.0
11.00R20	18	152/149	K	8.00	19.0

806

POSITION



- The overall pattern, similar to animals' spinal bones, is used both to strengthen the rigidity of the pattern in the center of the crown and to provide a better balance of the shoulders.
- Large horizontal pattern blocks and unique grooves deliver outstanding driving and braking performance.
- Narrow grooves enhance driving safety on wet skid road and provide excellent self-cleaning ability.



Size	PR	LI	SS	Standard Rim	OTD (mm)
10.00R20	18	149/146	K	7.50	17.0
11.00R20	18	152/149	K	8.00	17.5



807

POSITION



- Large lateral tread provides strong traction and prominent performance for the off-road.
- Reinforced tire bead and special designed mining pattern are suitable for bad road conditions and overloading.
- Good property of self-cleaning and high gripping performance suits for muddy road.

Size	PR	LI	SS	Standard Rim	OTD (mm)
9.00R20	16	144/142	K	7.0	20.0
10.00R20	18	149/146	K	7.5	22.5
11.00R20	18	152/149	K	8.0	23.0
12.00R20	20	156/153	K	8.5	23.0



808

POSITION



- Large block pattern ensures excellent performance of wear-resistance and tear-resistance.
- Deeper pattern improves tyres' service life.
- Convex groove bottom provides anti-stone performance and effectively prevents groove cracking.
- Low heating tread slab base ensures excellent durability and resistance to wear, cut and crack.

Size	PR	LI	SS	Standard Rim	OTD (mm)
9.00R20	16	144/142	E	7.0	22.5
10.00R20	18	149/146	E	7.5	23.5
12.00R20	20	156/153	E	8.5	24.0



809

POSITION



- Large lateral tread provides strong traction and prominent performance for the off-road.
- Optimized and reinforced tire bead and special designed mining pattern are suitable for bad road conditions and overloading.
- Large tread pattern with anti-cutting compound provides high resistance of cutting and stabbing, which especially suits for rough road like mine and quarry.

Size	PR	LI	SS	Standard Rim	OTD (mm)
11.00R20	18	152/149	E	8.0	23.0
12.00R20	20	156/153	E	8.5	24.5



897

POSITION



- Small cutter grooves provide the tyres with a strong grip performance and anti-slippery ability.
- Super wide running surface, specially processed shoulders with a tailor-made tread compound make wear resistance more remarkable.
- The inclined surface of zigzag grooves and the rubber protection at the bottom can effectively discharge clamped pebbles.

Size	PR	LI	SS	Standard Rim	OTD (mm)
9.00R20	16	144/142	K	7.0	15.5
10.00R20	18	149/146	K	7.5	16.5
11.00R20	18	152/149	K	8.0	17.0
12.00R20	20	156/153	K	8.5	17.5



899

POSITION



- Deeper block tread and wider tread cap enhance tyres' grip performance.
- Anti-stone function in the bottom of tread prevents the tyres from cutting of inner grooves in bad road conditions.
- Optimized and reinforced tire bead strengthens overloading ability.

Size	PR	LI	SS	Standard Rim	OTD (mm)
7.50R16LT	14	122/118	L	6.0G	16.0
8.25R16LT	16	128/124	L	6.50H	16.5
11.00R20	18	152/149	K	8.0	19.0
12.00R20	20	156/153	K	8.5	19.0



ECOSMART82

POSITION



- Deeper block tread and wider tread cap enhance tyres' grip performance.
- Anti-stone function in the bottom of tread prevents the tyres from cutting of inner grooves in bad road conditions.
- Optimized and reinforced tire bead strengthens overloading ability.

Size	PR	LI	SS	Standard Rim	OTD (mm)
12.00R24	20	160/157	K	8.5	20.0
325/95R24	22	162/160	K	9.0	20.0



696

POSITION



- Four longitudinal grooves provide the tyres with excellent handling stability and ride comfort at high speed.
- The shoulder cutter grooves and steel plate deliver good heat radiation and prevent irregular wear.
- The optimized tread arc ensures low rolling resistance and fuel conservation.

Size	PR	LI	SS	Standard Rim	OTD (mm)
11.00R20	18	152/149	K	8.0	15.0



686

POSITION



- Enhanced carcass steel wire and bead improve load performance.
- Optimized pattern makes the stress distribution more reasonable and prevents irregular wear.
- Four vertical lines and ladder-shaped grooves will lead to better heat dissipation.

Size	PR	LI	SS	Standard Rim	OTD (mm)
11.00R20	18	152/149	K	8.0	16.0



AH95

POSITION



- Block pattern provides strong traction and excellent tear resistance.
- Half-opened shoulders and wide transverse grooves provide strong driving force and excellent gripping ability in dry and wet road conditions.
- Unique tread compound provides excellent mileage.

Size	PR	LI	SS	Standard Rim	OTD (mm)
325/95R24	22	162/160	K	9.00	15.5



901

POSITION



- Mixed large tread, wide tread cap and deep tread pattern provide excellent traction.
- Optimized and reinforced tire bead, special designed mine pattern are made for rough road and overloading ability.
- Anti-cutting compound prevents cutting and stabbing, which especially suits for rough road.

Size	PR	LI	SS	Standard Rim	OTD (mm)
12.00R20	20	156/153	K	8.5	19.0



DM373

POSITION



- Provide a longer mileage.
- Provide excellent driving and grips performance.
- Enhance the grips performance on wet roads.
- Reduce tread heat generation, and deliver excellent durability.

Size	PR	LI	SS	Standard Rim	OTD (mm)
11R22.5	18	148/145	M	8.25	19.5
11R24.5	18	149/146	M	8.25	19.5



ECOSMART22

POSITION



- Provide a longer mileage.
- Provide excellent driving and grips performance.
- Enhance the grips performance on wet roads.
- Reduce tread heat generation, and deliver excellent durability.

Size	PR	LI	SS	Standard Rim	OTD (mm)
11R24.5	16	149/146	M	8.25	21.0
295/75R22.5	16	146/143	M	9.00	21.0
285/75R24.5	16	146/143	M	8.25	21.0



ECOSMART12

POSITION



- Possess excellent high-speed driving performance.
- Reduce uneven wear.
- Effectively reduce rolling resistance, and improve tire's drainage and stability performance.
- Low noise and high wear resistance.

Size	PR	LI	SS	Standard Rim	OTD (mm)
11R24.5	16	149/146	M	8.25	14.0
215/75R17.5	18	135/133	J	6.00	12.5
235/75R17.5	18	143/141	J	6.75	12.5
225/70R19.5	14	128/126	M	6.75	12.5
245/70R19.5	16	136/134	M	7.50	12.5
265/70R19.5	18	143/141	J	7.50	12.5
285/70R19.5	18	150/148	J	8.25	13.0
255/70R22.5	16	140/137	M	7.50	14.0
275/70R22.5	18	148/145	M	8.25	14.0
295/75R22.5	16	146/143	M	9.00	14.0
285/75R24.5	16	146/143	M	8.25	14.0



ECOSMART36

POSITION



- Possess excellent high-speed driving performance.
- Reduce uneven wear.
- Effectively reduce rolling resistance, and improve tire's drainage and stability performance.
- Suitable for long distance ride.

Size	PR	LI	SS	Standard Rim	OTD (mm)
11R24.5	16	149/146	M	8.25	11.0
295/75R22.5	16	146/143	M	9.00	11.0
285/75R24.5	16	146/143	M	8.25	11.0



ECOSMART77

POSITION



- Deliver high efficiency and environment protection.
- Constant grips and handling performance on wet roads.
- Provide a comfortable, safe and fuel saving ride.
- Provide better driving and wear resistance performance.

Size	PR	LI	SS	Standard Rim	OTD (mm)
425/65R22.5	20	165	J	12.25	17.5
445/65R22.5	20	169	K	13.00	18.0




ECOSMART78

POSITION



- Provide powerful driving and drainage performance.
- Improve the rigidity of tire's shoulder and prevent chipping.
- Greatly prolong tire's life.
- Add wear volume and improve wear resistance.

Size	PR	LI	SS	Standard Rim	OTD (mm)
215/75R17.5	18	135/133	J	6.00	15.0
235/75R17.5	18	143/141	J	6.75	15.0
225/70R19.5	14	128/126	M	6.75	15.0
245/70R19.5	16	136/134	M	7.50	15.0
265/70R19.5	18	143/141	J	7.50	15.0
285/70R19.5	18	150/148	J	8.25	16.0
275/80R22.5	16	149/146	M	8.25	19.0
315/70R22.5	18	152/148	M	9.00	20.0





YUELONG TIRE GROUP

Web: www.yuelonggroup.net

Email: info@yuelonggroup.net

DISTRIBUTED BY

www.yuelonggroup.net